



# Moticam 10

<b>Sensor Type</b>	CMOS
<b>Sensor Size</b>	1/2.3"
<b>Resolution</b>	10 MP
<b>Imaging Area</b>	6.12mm x 4.59mm
<b>Live Display Mode (through USB)</b>	3664 x 2748 @ 2.2 fps* 1296 x 972 @ 17 fps* 648 x 486 @ 26 fps*
<b>Pixel Size</b>	1.67µm x 1.67µm
<b>Scan Mode</b>	Progressive
<b>Data Transfer</b>	USB2.0
<b>Exposure Time</b>	0,16 msec to 10 sec
<b>Operating Temperature</b>	From -30 to +70 Degrees Celsius non condensing
<b>Max. Signal to Noise Ratio</b>	34dB
<b>Dynamic Range</b>	66.5dB
<b>Sensitivity</b>	0,31V/Lux-sec (550nm)
<b>Support Device</b>	TWAIN, SDK and Direct Show Driver
<b>Supported OS</b>	Microsoft Windows XP/Vista/7/8 and MAC OSX
<b>Minimum Computer Requirements</b>	2GHz multicore – RAM memory 2GB – Video memory min. 512 MB
<b>Lens Mount</b>	C-Mount
<b>Focusable Lens</b>	12mm
<b>Package Includes</b>	CS Ring Adaptor, Focusable Lens, 30mm and 38mm Eyepiece Adapters, USB 2.0 Cable, Calibration Slide, Macro Tube, Motic Images Plus 2.0 for PC and OSX

*\*frames per second under optimal illumination conditions*